

MATERIAL SAFETY DATA SHEET

CBT® 500 resin

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Cyclics Corporation
2135 Technology Drive
Schenectady, NY 12308

PHONE NUMBERS:

Emergency Information 518-881-1411
Non-Emergency Information 518-881-1411

PRODUCT IDENTIFIER:

CBT® 500 resin

PRODUCT DESCRIPTION:

Poly (butylene terephthalate) cyclized. 1,4-Benzenedicarboxylic acid, dimethylester, polymer with 1, 4-butanediol, CAS #263244-54-8.

PRODUCT USE:

May be used to produce molded articles or as a component of other industrial products.

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Components listed below are classified as hazardous as defined by the OSHA Hazard Communication Standard. The concentrations (expressed as weight percent) are typical or average values for this product. See also SECTION 15, REGULATORY INFORMATION.

Component Name	%	CAS Number	OSHA PEL	ACGIH TWA
None				

SECTION 3- HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Solid material that will burn in a fire creating dense, toxic smoke.

HMIS RATING:

Health 0, Flammability 1, Reactivity 0

POTENTIAL HEALTH EFFECTS

INGESTION:

No known adverse effects.

INHALATION:

No known adverse effects.

SKIN CONTACT:

No known adverse effects.

EYE CONTACT:

No known adverse effects.

NOTE:

CBT resin may cause skin or eye irritation in some individuals due to abrasive action of the resin in powder or granular form.

CHRONIC/CARCINOGENICITY

NTP:

Not tested

OSHA:

Not classified as a carcinogen

IARC:

Not listed as a carcinogen

SECTION 4 - FIRST AID MEASURES

EYES:	Flush eyes with large amount of clean, room temperature water for at least 15 minutes. After initial flushing remove contact lenses. If irritation persists seek medical attention promptly.
SKIN:	Remove contaminated clothing. Wash affected areas with soap and water. Seek medical attention if irritation persists.
INGESTION:	Not known to cause adverse health effects. Do not induce vomiting.
INHALATION:	Not known to cause adverse health effects. Leave contaminated area and get fresh air.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE FIGHTING:	Fight fire from a safe distance with proper personal protective equipment including self-contained breathing apparatus.
EXTINGUISHING MEDIA:	Water spray, foam. Carbon dioxide and dry chemical are not recommended because their lack of cooling capacity may permit re-ignition.
CONDITIONS OF FLAMMABILITY:	Requires a continuous flame source to ignite.
FLASH POINT:	None
AUTOIGNITION TEMPERATURE:	380 c (680 F)
EXPLOSION DATA:	Material is not sensitive to mechanical impact, but finely ground materials is sensitive to static discharge under dust cloud conditions. In limited testing with CBT resin dust (-200 mesh), a minimum concentration of 35 gm/m ³ . and minimum ignition energy of 0.4 joules were required to form an explosive dust cloud.
EXPLOSION LIMITS:	NA
HAZARDOUS COMBUSTION PRODUCTS:	Intense heat, black smoke, carbon dioxide, carbon monoxide.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

GENERAL:	Sweep up spillage and reuse or dispose, as appropriate. Insure that molten resin has thoroughly cooled before disposal.
----------	---

SECTION 7 - HANDLING AND STORAGE

HANDLING:	Use good industrial hygiene practices and provide adequate ventilation. Secondary operations on molded parts (such as grinding, sanding or sawing) could produce an explosion hazard if dust is not adequately controlled. Use adequate ventilation and aggressive housekeeping practices to prevent dust accumulation.
-----------	---

STORAGE: Store resin on pallets in a cool, dry covered area to maintain the integrity of the packing material. Do not stack more than two units high (pallets, drums, or boxes). Do not store in areas near open flame(s) or other potential ignition sources.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Fumes generated during thermal processing of CBT resin may cause irritation in some individuals. Minimize exposures through controlled exhaust and fresh air makeup.

PERSONAL PROTECTION:

GENERAL: Grinding, sanding or sawing plastic parts can produce airborne particles.

EYE/FACE: Wear safety glasses with side shields or chemical goggles, as appropriate.

SKIN: Avoid prolonged or unnecessary direct contact with resin granules/powder.

RESPIRATORY: Wear a well-fitting dust respirator if area ventilation is insufficient.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Solid

ODOR AND APPEARANCE: Off white plastic pellets/granules/powder. Slight, mild odor.

MELTING POINT: Melts between 120 – 200 C.

VAPOR PRESSURE (mm Hg): Nil

SPECIFIC GRAVITY (water=1): 1.3

WATER SOLUBILITY: <0.3 ppm

% VOLATILES: <1.0

EVAPORATION RATE: Nil

OCTANOL / WATER PARTITION COEFFICIENT: 3.52

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: Stable.

REACTIVITY: Not reactive under recommended conditions of handling and storage.

CONDITIONS TO AVOID: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: None. Hazardous polymerization will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE ORAL: LD-50:greater than 5g/kg (rat), based on tests of similar material (poly-butylene terephthalate).

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: This material is not known to be harmful to the environment. Decomposition is not expected to produce toxic waste products. This material facilitates the recycling and reuse of polyester resins. Plastic particles

produced using this material can be recycled and used in the manufacture of other plastic parts.

SECTION 13 - DISPOSAL INFORMATION

DISPOSAL: This resin is not RCRA regulated hazardous waste. Recycling should always be considered as the first and most desirable option. If not recyclable, then dispose of in accordance with applicable local, state and federal regulations. See also Section 15 – Regulator Information.

SECTION 14 - TRANSPORTATION INFORMATION

STATUS: This resin is not classified as a hazardous material for transportation purposes.

SECTION 15 - REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA): CBT resin is listed on the public US TSCA Chemical Substance Inventory.

SUPPLIER NOTIFICATION REQUIREMENTS: As a new and innovative chemical, CBT is currently regulated by the EPA/TSCA under the “Significant New Use Rules” (SNUR). Obligations imposed by this SNUR apply equally to all users. The SNUR specifically requires that this material be stored, handled, processed and disposed without a predictable or purposeful release to surface waters. Please contact us directly if you have questions regarding this requirement.

EU REGULATOR NOTIFICATION: As stated by Council Directive 92/32/EEC dated April 30, 1992, CBT resin is exempt from notification as a new substance in the European Union because it meets the definition of a polymer and is comprised solely of EINECS-listed monomers.

SECTION 16 - OTHER INFORMATION

DISCLAIMER: This Material Safety data Sheet (MSDS) information is provided based on the requirements of Hazard Communication Regulations. Cyclics Corporation does not warrant the suitability for use of this MSDS for any other material or product not specifically identified herein. Cyclics Corporation does not warrant the accuracy or authenticity of this MSDS unless it was obtained directly from Cyclics Corporation, or posted or viewed on the Cyclics Corporation website. Modification of this MSDS, unless specifically authorized by Cyclics Corporation, is strictly prohibited. This MSDS is based on information which is believed to be reliable, but may be subject to change as new information becomes available. Since it is not possible to anticipate all conditions of use, additional safety precautions may be required. As the use of this material is not under Cyclics Corporation’s control, each user is responsible for making its own determination as to the safe and proper handling of this material in its own particular use of this material. **CYCLICS CORPORATION MAKES NO REPRESENTATION OR WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING AS TO THE MERCHANTABILITY OR FITNESS FOR A PARTICULAR APPLICATION OR PURPOSE.**

PREPARED BY: Robert Lindberg – Director, EHS

ABBREVIATIONS

ACGIH: American Conference of Governmental Industrial Hygienists.

CAS: Chemical Abstracts service

HMIS: Hazardous Material Information System

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit

PPE: Personal Protective Equipment

TWA: Time Weighted Average

"Cyclics", "Cyclics Corporation", and "CBT" are registered trademarks of Cyclics Corporation in the United States and other countries.